

Profiles

Use: Roof/Wall/Liner

Slope: 3/12 and greater


Coverage: 36" width

Lengths: 3' to 45'

Rib Height: 3/4" on 9" centre

Recommended Substrate: Solid or Open Frame

9-36



Gauge: 29 ga, 26 ga, 24 ga

Exposed Fastener

Use: Roof/Wall/Liner

Slope: 1/12 and greater


Coverage: 35" (26 ga), 36" (24ga)

Lengths: 3' to 45'

Rib Height: 7/8" on 2.66" centre

Recommended Substrate: Solid or Open Frame

7/8" Corrugated



Gauge: 26 ga, 24 ga, 22 ga

Exposed Fastener

Use: Roof/Wall

Slope: 1/12 and greater


Coverage: 36" width

Lengths: 3' to 45'

Rib Height: 1.5" on 12" centre

Recommended Substrate: Solid or Open Frame

12-36



Gauge: 26 ga, 24 ga, 22 ga

Exposed Fastener

Use: Roof/Wall

Slope: 3/12 and greater


Coverage: 36" width

Lengths: 3' to 45'

Rib Height: 3/4" on 6" centre

Recommended Substrate: Solid or Open Frame

Diamond Rib



Gauge: 26 ga, 24 ga

Exposed Fastener

Use: Wall/Liner


Coverage: 36" width

Lengths: 3' to 45'

Rib Height: 1.5" reversed on 12" centre

Recommended Substrate: Solid or Open Frame

12-36 Reverse



Gauge: 26 ga, 24 ga, 22 ga

Exposed Fastener

Use: Wall/Liner


Coverage: 36" width

Lengths: 3' to 45'

Rib Height: 3/4" reversed on 6" centre

Recommended Substrate: Solid or Open Frame

Diamond Rib Reverse



Gauge: 26 ga, 24 ga

Exposed Fastener

Use: Curved Roof/Wall/Liner


Coverage: 36" width

Lengths: 3' to 45'

Rib Height: 3/8" on 9" centre

Recommended Substrate: Solid

Low Rib



Gauge: 29 ga, 26 ga

Exposed Fastener

Use: Wall/Liner

Coverage: 37.25" (29 ga)

41.25" (26 ga)

Lengths: 3' to 12'

Recommended Substrate: Solid

Mesa



Gauge: 29 ga, 26 ga

Exposed Fastener

Use: Roof

Slope: 1/12 and greater


Coverage: 12" to 24" width

Lengths: 3' to 45'

Rib Height: 1", 1-1/2", or 2"

Recommended Substrate: Solid

Standing Seam



*Available to Curve 1 1/2" height 24-22 ga only

Gauge: 26 ga, 24 ga, 22 ga

Hidden Fastener

Use: Roof

Slope: 3/12 and greater


Coverage: 12" to 20" width

Lengths: 3' to 45'

Rib Height: 1"

Recommended Substrate: Solid

Snaplock



Gauge: 26 ga, 24 ga, 22 ga

Hidden Fastener